INDUSTRIAL COMPONENT DATA

TML (EX7)R SR CUS 0830851 PHOENIX CONTACT Marking foil for zack marker strip

Brand: PHOENIX CONTACT | Manufacturer Part Number: TML (EX7)R SR CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	TML (EX7)R SR CUS
Catalog number	0830851
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-2EBBADF847
Generated	2026-11-19

Product Overview

Marking foil for zack marker strip
Zack strip wrapping film, Roll, available: by lines, silver, labeled according to customer's instructions, labelable with: THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting class: glued, for terminal width: 30000 mm, usable area: 30000 x 7 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 0830851
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4046356897341
Weight per Piece (excluding packing) 1.990 g
Custom tariff number 39199080
Country of origin DE (Germany)
Dimensions
Length (b) 30 m
Width (a) 7 mm
Ambient conditions

Recommended storage conditions 23 °C / 50% relative humidity. Storage in the original packaging is recommended prior to processing.
General
Color silver
Type adhesive
RoHS compliant Yes
Adhesive Acrylic
Printability Thermal transfer
Device 5146477 THERMOMARK ROLL
5146231 THERMOMARK X1.2
Ink ribbon 5145384 THERMOMARK-RIBBON 110
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Foil strength 53 µm
Adhesive strength 20 µm
Marking mounting type adhesive
Classifications
eCl@ss 4.124190208eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss 7.027141137eCl@ss 8.027141137eCl@ss 9.027141137
ETIM 4.0EC000761ETIM 5.0EC000761ETIM 6.0EC000761
UNSPSC 13.239131505

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TML (EX7)R SR CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.