

INDUSTRIAL COMPONENT DATA

TP 3070W/WT-65 SER 1034352 PHOENIX CONTACT Touch panel TP 3070W/WT-65 SER 1034352

Brand: PHOENIX CONTACT | Manufacturer Part Number: TP 3070W/WT-65 SER



Manufacturer	PHOENIX CONTACT
MPN / Reference	TP 3070W/WT-65 SER
Catalog number	1034352
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-7123E8DEA1
Generated	2026-09-23

Product Overview

Touch panel - TP 3070W/WT-65 SER - 1034352

Rugged touchpad with 17.8 cm/7" TFT display (analog-resistive (GFG)), 800 x 480 pixels (WVGA), IP65 (front), extended temperature range, 1x COM (RS-232), 1x COM (RS-422/485), Arm®Cortex®-A8, 1000 MHz, Windows®Embedded Compact 7 and Visu+ user software.

Rugged touch panel with 17.8 cm / 7" TFT display (analog-resistive (GFG)), 800 x 480 pixels (WVGA), degree of protection: IP65 (front), extended temperature range, 1x COM (RS-232), 1x COM (RS-422/485), Arm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Control Systems (CST)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1034352

Packing unit 1

GTIN 4055626540481

Custom tariff number 84714100

Note

Display

General

Device supply

Environmental Product Compliance

Dimensions

Computer data

Ambient conditions

Standards and Regulations

Classifications

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

[Back to top](#)Dimensions

Outer dimensions: width, height, depth 208 mm x 148 mm x 5 mm (Dimensions of the front plate)

Installation dimensions: width, height, depth 200 mm x 140 mm x 75 mm (Mounting cutout, depth with bus if bus system present in the device)

[Back to top](#)Display

Display 17.8 cm/7" TFT

Screen resolution 800 x 480 Pixel(s) (WVGA)

Touch technology Analog resistive (GFG)

Brightness 400 cd/m², typical (adjustable)

Backlighting LED

Display backlight MTBF 50000 h

Colors 16.7 million colors

Reading angle left 70 °

Reading angle right 70 °

Reading angle top 60 °

Reading angle bottom 60 °

[Back to top](#)Computer data

Operating system Windows® Embedded Compact 7

User software Visu+

RAM 1 MB SRAM

512 MB LPDDR SDRAM

Mass storage NAND-Flash, 256 MB

Network 1 x Ethernet (10/100 Mbps), RJ45

Interfaces 2x USB Host 2.0

1x COM (RS-232)

1x COM (RS-422/485)

Slots 1x SD

Realtime clock Yes

Service life of battery 5 years (typical)

[Back to top](#)General

Extras Integrated acoustic signal (buzzer)

Material front plate Aluminum (natural anodized)

Housing material Steel sheet, zinc-plated

Mounting type Bolt fixing

Weight 1100 g

[Back to top](#)Ambient....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TP 3070W/WT-65 SER with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.