INDUSTRIAL COMPONENT DATA

MCR-SL-S-200-I-LP 2813499 PHOENIX CONTACT Current transducers

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCR-SL-S-200-I-LP



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCR-SL-S-200-I-LP
Catalog number	2813499
Category	Current value transformer
Minimum order	1 Pcs
Document ID	EO-B522BA47E2
Generated	2026-11-18

Product Overview

Current transducers
MCR current converter, for measuring sinusoidal and non-sinusoidal alternating currents, input current 0...200 A, Loop-powered output with 4...20 mA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2813499
Packing unit 1 pc
Catalog page Page 247 (C-5-2017)
GTIN 4046356043670
Weight per Piece (excluding packing) 144.500 g
Custom tariff number 85437090
Country of origin JP (Japan)
Dimensions
Primary round conductor (diameter) 18.5 mm
Width 55 mm
Height 85 mm
Depth 70.5 mm

Ambient conditions
Ambient temperature (operation) -20 °C ... 60 °C
Input data
Input Current measuring input
Input current range 0 A ... 200 A (0 ... 100/150/200 A)
Operate threshold 1 % (of final value)
Setting range for min. input current 0 A ... 100 A
Setting range for max. input current 0 A ... 200 A
Overload capacity Depending on laid conductor
Surge strength Depending on through connected conductor
Frequency measuring range 30 Hz ... 6000 Hz
Output data
Output name Current output
Current output signal 4 mA ... 20 mA
Max. output current < 25 mA
Load/output load current output (UB- 12 V) x 350 / 12 A
Switching output
Output name No switching output
Power supply
Supply voltage range 20 V DC ... 30 V DC
Connection data
Connection method Pluggable screw connection
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 14
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Stripping length 8 mm
Screw thread M3
General
Maximum transmission error < 1 % (of final value)
Maximum temperature coefficient < 0.025 %/K
Step response (10-90%) < 34...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCR-SL-S-200-I-LP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.