INDUSTRIAL COMPONENT DATA

# PACT MCR-V2-5012- 85-1500-5A-1 2276188 PHOENIX CONTACT Current transformer

**Brand: PHOENIX CONTACT | Manufacturer Part Number: PACT MCR-V2-5012-85-1500-5A-1**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | PACT MCR-V2-5012-85-1500-5A-1 |
| Catalog number | 2276188 |
| Category | Current transformer |
| Minimum order | 1 Pcs |
| Document ID | EO-4E6EB73D32 |
| Generated | 2026-11-18 |

## Product Overview

Current transformer
Transformer through bar current, primary current 1500 A AC; secondary current 5 A AC; accuracy class 1; Sizing power 15 VA

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > INTERFACE Components (IF) |

## Additional Product Information

Key Commercial Data
Orderkey 2276188
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 226 (C-5-2017)
GTIN 4046356502481
Weight per Piece (excluding packing) 564.700 g
Custom tariff number 85043129
Country of origin DE (Germany)
Dimensions
Primary round conductor (diameter) 42 mm
Primary round conductor (width) 50 mm
Primary round conductor (height) 12 mm

Note on dimensions 2
Primary round conductor (width) 40 mm
Primary round conductor (height) 10 mm
Width 30 mm
Height 108 mm
Depth 85 mm
Width with alternative assembly 85 mm
Height with alternative assembly 108 mm
Depth with alternative assembly 30 mm
Ambient conditions
Ambient temperature (operation) -25 °C ... 40 °C
Ambient temperature (storage/transport) -25 °C ... 40 °C
Maximum altitude <= 1000 m
Input data
Number of inputs 1
Thermal rated short-time current Ith= 60 * In
Thermal rated continuous current Id= 1.2 * In
Rated surge current Idyn= 2.5 * Ith
Rated frequency: Standard converter 50 Hz ... 60 Hz
Rated frequency: Calibrated converter 50 Hz
Surge current limitation factor FS 5
Rated power 15 VA
Primary rated current Ipn 0 A ... 1500 A
Secondary rated current Isn 5 A AC
Output data
Connection method Screw connection
General
Converter type Plug-on converters
Accuracy class 1
Can be calibrated no
Rated insulation voltage 1 kV (Phase/neutral conductor)
Standards/regulations EN 50178
EN 61869
Color black
Housing material PA 6.6
UL, USA/Canada XODW8.E323953
Standards and Regulations
Standards/regulat...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PACT MCR-V2-5012-85-1500-5A-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.