INDUSTRIAL COMPONENT DATA

TTC-6-3-HF-F-M-12DC-UT-I 2906769 PHOENIX CONTACT Surge protection with integrated status indicator and knife..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TTC-6-3-HF-F-M-12DC-UT-I



Manufacturer	PHOENIX CONTACT
MPN / Reference	TTC-6-3-HF-F-M-12DC-UT-I
Catalog number	2906769
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-52324F20F8
Generated	2026-11-19

Product Overview

Surge protection with integrated status indicator and knife disconnection for three signal wires with common reference potential. For HF applications and telecommunications interfaces without supply voltage (up to 90 Mbps). Indirect grounding via gas-filled surge arrester.
Surge protection with integrated status indication and blade separation for three signal conductors with common reference potential. For high-frequency applications and telecommunication interfaces without supply voltage (up to 90 MBit/s). Indirect grounding by gas discharger.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data
Orderkey 2906769
Packing unit 1 pc
Catalog page Page 171 (C-4-2019)
GTIN 4055626135182
Weight per Piece (excluding packing) 40.000 g
Custom tariff number 85363010
Country of origin DE (Germany)
Drawings
Ambient conditions

Protective circuit
Connection data
Environmental Product Compliance
Dimensions
General
Additional technical data
Standards and Regulations
Classifications
Drawings
Diagram
Dimensional drawing
Circuit diagram
Back to topDimensions
Height 105.8 mm
Width 6.2 mm +0.1 mm
Depth 83.5 mm (incl. DIN rail 7.5 mm)
Back to topAmbient conditions
Ambient temperature (operation) -40 °C ... 85 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Permissible humidity (operation) 5 % ... 95 %
Altitude <= 4000 m (amsl (above mean sea level))
Degree of protection IP20
Back to topGeneral
Housing material PBT
Flammability rating according to UL 94 V-0
Color traffic grey A RAL 7042
Mounting type DIN rail: TH 35 - 7.5 mm
Type DIN rail module, one-piece
Direction of action Line-Line & Line-Signal Ground/Shield & optional Signal Ground/Shield-Earth Ground
Back to topProtective circuit
IEC test classification C1
C2
C3
D1
Nominal voltage UN 12 V DC
Maximum continuous voltage UC 15 V DC
10 V AC
Rated current 600 mA (40 °C)
Operating effective current ICat UC <= 100 µA
Residual current IPE <= 1 µA
Nominal discharge current In(8/20) µs (line-line) 5 kA
Nominal discharge current In(8/20) µs (line-earth) 5 kA
Nominal discharge current In(8/20) µs (line-signal ground...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TTC-6-3-HF-F-M-12DC-UT-I with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.