INDUSTRIAL COMPONENT DATA

TTC-6-GDT-C-24AC-UT-I 2906842 PHOENIX CONTACT Coarse surge protection with integrated status indicator for a..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TTC-6-GDT-C-24AC-UT-I



Manufacturer	PHOENIX CONTACT
MPN / Reference	TTC-6-GDT-C-24AC-UT-I
Catalog number	2906842
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-9E59AA29B0
Generated	2026-11-19

Product Overview

Coarse surge protection with integrated status indicator for a signal wire with grounded reference potential.
Sufficient surge protection with integrated status indication for a signal conductor with grounded reference potential.
Coarse surge protection with integrated status indicator for a signal wire with grounded reference potential. Can be used in safety-related circuits up to SIL 3.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Technical dataProduct propertiesProduct type Surge protection for MCR technology
Product family TERMITRAB complete
IEC test classification C1
C2
C3
D1
Type DIN rail module, one-piece
Surge protection fault message optical
Data management status
Article revision 08
Insulation characteristics
Overvoltage category III

Pollution degree 2
Electrical propertiesNominal voltage UN 24 V AC
Connection dataConnection method Screw connection
Screw thread M3
Tightening torque 0.5 Nm ... 0.6 Nm
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section rigid 0.2 mm² ... 4 mm²
Conductor cross section AWG 24 ... 12
DimensionsDimensional drawing
Width 6.2 mm
Height 92 mm
Depth 69.5 mm (incl. DIN rail 7.5 mm)
Material specificationsColor gray (RAL 7042)
Flammability rating according to UL 94 V-0
Insulating material PBT
Housing material PBT
Mechanical propertiesMechanical data
Open side panel Yes
Protective circuitDirection of action Line-Earth Ground
Maximum continuous voltage UC 28 V DC
36 V AC
Rated current 1 A DC (60 °C)
2 A AC (60 °C)
Operating effective current ICat UC <= 1 µA
Residual current IPE <= 1 µA
Nominal discharge current In(8/20) µs (line-ground) 5 kA
Pulse discharge current Iimp(10/350) µs (line-earth) 0.5 kA
Voltage protection level Up(line-earth) <= 800 V (C1 - 2 kV)
<= 1 kV (C2 - 10 kV)
<= 800 V (C3 - 25 A)
<= 900 V (C3 - 100 A)
Response time tA(line-earth) <= 100 ns
Input attenuation aE, asym. typ. 0.3 dB (<= 8 MHz/150 ?)
typ. 0.3 dB (<= 30 MHz/50 ?)
Cut-off frequ...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TTC-6-GDT-C-24AC-UT-I with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.