INDUSTRIAL COMPONENT DATA

TTC-6-MOV-D-120AC-PT-I 1109689 PHOENIX CONTACT Medium surge protection with integrated status indicator for ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TTC-6-MOV-D-120AC-PT-I



Manufacturer	PHOENIX CONTACT
MPN / Reference	TTC-6-MOV-D-120AC-PT-I
Catalog number	1109689
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-93D7FEA809
Generated	2026-11-19

Product Overview

Medium surge protection with integrated status indicator for a 2-wire floating signal circuit.
Medium surge protection with integrated status indication for a potential-free 2-wire signal circuit.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data
Orderkey 1109689
Packing unit 1 pc
GTIN 4063151020170
Weight per Piece (excluding packing) 0.000 g
Custom tariff number 85363010
Country of origin DE (Germany)
Drawings
Ambient conditions
Protective circuit
Standards and Regulations
Dimensions
General
Connection data

Classifications
Drawings
Diagram
Dimensional drawing
Circuit diagram
Back to topDimensions
Height 92 mm
Width 6.2 mm
Depth 69.5 mm (incl. DIN rail 7.5 mm)
Back to topAmbient conditions
Ambient temperature (operation) -40 °C ... 85 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Permissible humidity (operation) 5 % ... 95 %
Altitude <= 2000 m (amsl (above mean sea level))
Degree of protection IP20 (with end cover)
Back to topGeneral
Housing material PBT
Flammability rating according to UL 94 V-0
Color traffic grey A RAL 7042
Mounting type DIN rail: 35 mm
Type DIN rail module, one-piece
Direction of action Line-Earth Ground
Back to topProtective circuit
IEC test classification C1
C2
C3
Nominal voltage UN 120 V AC
Maximum continuous voltage UC 150 V DC
150 V AC
Rated current 10 A (60 °C)
Operating effective current ICat UC <= 100 µA
Residual current IPE <= 100 µA
Nominal discharge current In(8/20) µs (line-line) 2.5 kA
Voltage protection level Up(line-line) <= 200 V (C1 - 800 A)
<= 500 V (C2 - 5 kV)
<= 380 V (C3 - 25 A)
<= 380 V (C3 - 35 A)
Response time tA(line-line) <= 25 ns
Input attenuation aE, sym. typ. 0.3 dB (<= 300 kHz / 150 ?)
Cut-off frequency fg (3 dB), sym. in 150 Ohm system typ.....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TTC-6-MOV-D-120AC-PT-I with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.