INDUSTRIAL COMPONENT DATA

TU-00000004100X 1242016 PHOENIX CONTACT Recessed housing, straight, Bayonet lock, M23, number of poles: 12, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TU-00000004100X



Manufacturer	PHOENIX CONTACT
MPN / Reference	TU-00000004100X
Catalog number	1242016
Category	Housing for circular connectors
Minimum order	1 Pcs
Document ID	EO-C678F5DC17
Generated	2026-11-19

Product Overview

Recessed housing, straight, Bayonet lock, M23, number of poles: 12, contact connection type: Female, Flat joint, 4xM3, shielded: yes, protection index: IP67, connection type: Crimp connection, series: TU, The item does not contain lead according to the RoHS II directive without exception 6c (Pb&lt.; 0.1%)
Housing Gland, Straight, Bayonet Lock, M23, Number of Poles: 12, Contact Type: Female, Flat Gasket, 4xM3, Shielded: Yes, Degree of Protection: IP67, Connection Type: Crimped Connection, Series: TU, Item Lead-Free According to RoHS II Directive, Excluding 6c (Pb< 0.1%)
Housing screw connection, straight, Bayonet locking, M23, number of positions: 12, contact connection type: Socket, Flat gasket, 4xM3, shielded: yes, degree of protection: IP67, connection method: Crimp connection, series: TU, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT

Additional Product Information

Technical dataNotesGeneral Order contact inserts separately
Product propertiesProduct type Panel mounting base
Connection profile 12
Application Signal
Series TU
Shielded yes
Thread type M23

Connection dataConnection method Crimp connection
DimensionsDimensional drawing
Length of the solder pin 16.5 mm
2.5 mm
3.5 mm
9 mm
16.5 mm
2.5 mm
3.5 mm
9 mm
Material specificationsSeal material FPM or NBR or EPDM
Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Gasket and O-ring material FPM
Housing material Metal
ConnectorType straight
Environmental and real-life conditionsAmbient conditions
Degree of protection IP67
MountingMounting 4x M3
Panel thickness < 2.5 mm
Connection method Crimp connection

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TU-00000004100X with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.