INDUSTRIAL COMPONENT DATA

BLT-T2-1S-320-UT 2906101 PHOENIX CONTACT Type 2 surge arrester

Brand: PHOENIX CONTACT | Manufacturer Part Number: BLT-T2-1S-320-UT



Manufacturer	PHOENIX CONTACT
MPN / Reference	BLT-T2-1S-320-UT
Catalog number	2906101
Category	Surge protection device for power supply systems
Minimum order	10 Pcs
Document ID	EO-B2D392FB5B
Generated	2026-11-19

Product Overview

Type 2 surge arrester
Type 2 surge arrester for universal mounting on lights, cable junction boxes, installation boxes, wall channels, underfloor installations or directly on terminal equipment. Special for insulation protection class I with optical defect notification. Installation in branch or pass-through wiring. Construction: 230 V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data
Orderkey 2906101
Packing unit 10 pc
Minimum order quantity 10 pc
Catalog page Page 69 (C-4-2017)
GTIN 4055626058085
Weight per Piece (excluding packing) 44.840 g
Custom tariff number 85363030
Country of origin CN (China)
Dimensions
Height 56 mm
Width 36.5 mm

Depth 34 mm
Ambient conditions
Degree of protection IP20
Ambient temperature (operation) -40 °C ... 80 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Altitude <= 2000 m (amsl (above mean sea level))
Permissible humidity (operation) 5 % ... 95 %
General
IEC test classification II / III
T2 / T3
EN type T2 / T3
IEC power supply system TN-S
TT
Mode of protection L-N
L-PE
N-PE
Mounting type 4 mm screw
Color light grey RAL 7035
Housing material PA 6.6
Degree of pollution 2
Flammability rating according to UL 94 V-0
Protection class I
Type Installation module
Surge protection fault message optical
Protective circuit
Nominal voltage UN 100 V AC ... 277 V AC (TN-S)
100 V AC ... 277 V AC (TT)
Nominal frequency fN 50 Hz (60 Hz)
Maximum continuous operating voltage UC(L-N) 320 V AC
Maximum continuous operating voltage UC(L-PE) 305 V AC
Maximum continuous voltage UC(N-PE) 305 V AC
Rated load current IL 16 A
Residual current IPE <= 5 µA
Nominal discharge current In(8/20) µs (L-N) 5 kA
Nominal discharge current In(8/20) µs (L-PE) 5 kA
Nominal discharge current In(8/20) µs (N-PE) 10 kA
Maximum discharge current Imax(8/20) µs (L-N) 10 kA
Maximum discharge current Imax(8/20) µs (L-PE) 10 kA
Maximum discharge...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BLT-T2-1S-320-UT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.