INDUSTRIAL COMPONENT DATA

# UBE/D (60X10) 0803719 PHOENIX CONTACT Marker carriers

**Brand: PHOENIX CONTACT | Manufacturer Part Number: UBE/D (60X10)**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | UBE/D (60X10) |
| Catalog number | 0803719 |
| Category | Mounting for labelling material |
| Minimum order | 50 Pcs |
| Document ID | EO-23CE901884 |
| Generated | 2026-11-19 |

## Product Overview

Marker carriers
Support for indexes for terminal strips, for the identification of terminal groups, for mounting on the NS 32 or NS 35/7.5 terminal strip, callout size: 60 x 10 mm

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > MS Material |

## Additional Product Information

Key Commercial Data
Orderkey 0803719
Packing unit 50 pc
Minimum order quantity 50 pc
Catalog page Page 587 (C-3-2017)
GTIN 4055626146263
Weight per Piece (excluding packing) 8.040 g
Custom tariff number 39269097
Country of origin DE (Germany)
Dimensions
Length (b) 48.5 mm
Width (a) 10 mm
Height (c) 60 mm
Ambient conditions

Ambient temperature (operation) -40 °C ... 100 °C
General
Color gray
Base element material PA
Components free from silicone and halogen
Flammability rating according to UL 94 V0
Material PA
RoHS compliant Yes
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type DIN rail mounting
Result Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
Class I 2
Class F 2
Surface flammability (ASTM E 162) passed
Specific optical density of smoke (ASTM E 662) passed
Smoke gas toxicity (SMP 800C) passed
Heat dissipation calorimetric (ASTM E 1354) 28 MJ/kg
R22 HL 1 - HL 3
R23 HL 1 - HL 3
R24 HL 1 - HL 3
R26 HL 1 - HL 3
Standards and Regulations
Flammability rating according to UL 94 V0
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Classi...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UBE/D (60X10) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.



Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.