INDUSTRIAL COMPONENT DATA

UC-17S1N8AQ0DU 1606598 PHOENIX CONTACT Rear panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: UC-17S1N8AQ0DU



Manufacturer	PHOENIX CONTACT
MPN / Reference	UC-17S1N8AQ0DU
Catalog number	1606598
Category	Circular connector, mounting (without cable)
Minimum order	10 Pcs
Document ID	EO-F780AAE619
Generated	2026-11-19

Product Overview

Rear panel feed-through
M23, Rear wall pass-through, UC, straight, shielded: yes, Screw lock, No. of poles: 17, Direction of rotation: Standard, contact type: Female, Crimped connection, Axial O-ring, Central fixing, coding:N, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1242172
M23, Rear panel feed-through, series: UC, straight, shielded: yes, Screw locking mechanism, No. of pos.: 17, Direction of rotation: Standard, contact connection type: Socket, Crimp connection, Axial O-ring, Central fixing, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataProduct propertiesProduct type Circular connector (cable-side)
ConnectorInsulating body
Note Order information: Order crimp contacts Ø 1 mm separately
Coding N
Connection method Crimp connection
Contact switching type Socket
Application Signal
Number of positions 17
Direction of rotation Standard

Connection profile 17
Contact diameterPower contacts 1 mm
Rated currentPower contacts 8 A
Rated voltage 48 V AC
74 V DC
Rated surge voltage 1.5 kV
Overvoltage category III
Degree of pollution 3
Housing
Housing material Metal
Type of locking Screw locking mechanism
Pg screw connection none
Degree of protection (plugged in) IP67
Thread type M23
Environmental and real-life conditionsAmbient conditions
Ambient temperature (storage/transport) 15 °C ... 25 °C
Permissible humidity (storage/transport) 50 % ... 65 %

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UC-17S1N8AQ0DU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.