INDUSTRIAL COMPONENT DATA

UC-WMTBA (29X8)/PP YE CUS 1541711 PHOENIX CONTACT Cable marker, available: matted, yellow, labelled accordin..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UC-WMTBA (29X8)/PP YE CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UC-WMTBA (29X8)/PP YE CUS
Catalog number	1541711
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-1C975A5F40
Generated	2026-11-18

Product Overview

Cable marker, available: matted, yellow, labelled according to customer specifications, mounting class: Mounting with cable tie, cable diameter: &gt.; 6 mm, usable area: 29 x 8 mm, Number of individual indexes: 12
Cable Marker
Cable marker, can be ordered: by sheet, yellow, labeled according to customer specifications, mounting type: Assembly with cable ties, cable diameter: > 6 mm, lettering field size: 29 x 8 mm, Number of individual labels: 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Technical dataProduct propertiesProduct type Conductor marking
Type Card form
Marking
Number of individual labels 12
Number of individual labels per row 4
Identification technology Direct laser marking
DimensionsWidth 13.5 mm
Length 29 mm
External dimensions
Outside diameter > 6 mm ... 136 mm
Material specificationsColor yellow

Material PP
Components free from silicone and halogen
Cable/lineExternal cable diameter > 6 mm
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
Test for substances that would hinder coating with paint or varnish
Result Test passed
Scratch test for the determining scratch resistance
Specification DIN EN ISO 1518-1:2019-10 (following)
Requirements >= 5 N
Result Test passed
Tesafilm test
Specification DIN EN ISO 2409:2013 (following)
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03
Result Test passed
Test duration 96 h
Specification IEC 60068-2-2:2007-07
Result Test passed
Duration 96 h
Maximum temperature +85 °C
Temperature resistance
Specification ANSI/UL 969-2018:03 (following)
Test duration 240 h
Rating 125 °C (150 °C) Test passed
Specification ISO 175:2010 (following)
Test duration 168 h
Diesel
[CAS No. 68476-34-6] Test passed
IRM 901 Test passed
IRM 902 Test passed
Testing in a condensation changing climate in the presence of sulfur dioxide
Specification DIN 50018:2013-05
Result Test passed
Climate level AHT 1.0 S
Cycles 2
Salt spray test
Specification DIN E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UC-WMTBA (29X8)/PP YE CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.