INDUSTRIAL COMPONENT DATA

UCS CCD 5015 1056065 PHOENIX CONTACT Corner inlay for UCS housings with integrated screw boss material: poly..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS CCD 5015



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS CCD 5015
Catalog number	1056065
Category	Extruded profile modular housing
Minimum order	1 Pcs
Document ID	EO-85A2FAB7DE
Generated	2026-11-18

Product Overview

Corner inlay for UCS housings with integrated screw boss; material: polyamide; color: sky blue, similar to RAL 5015
Angular inserts for UCS housings with integrated threaded mandrel; Material: Polyamide; Color: Sky Blue, similar to RAL 5015

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1056065
Packing unit 1
GTIN 4055626695006
Custom tariff number 39269097
Item properties
Material specifications
PCB data
Packaging information
Classifications
Measurements
Ambient conditions
Note on mounting

Standards and regulations
Item properties
Type UCS CCD 5015
Order No. 1056065
Housing type Universal housings
Type Including flat screws and screws for PCB mounting
Back to topMeasurements
Width [w] 16.2 mm
Height [h] 16.2 mm
Depth [d] 27.05 mm
Back to topMaterial specifications
Color (RAL) sky blue (5015)
Insulating material PA
Flammability rating according to UL 94 V0
Housing material PA
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Back to topPCB data
Note on PCB holders This product is prepared for a printed-circuit board. Additional printed-circuit boards can be mounted using adhesive pads (accessories).
PCB thickness 0.8 mm ... 3 mm
Type of PCB mount Bolt mounting
Back to topNote on mounting
Drive form screw head Mounting the PCB: Slotted Torx®(T7)
Back to topPackaging information
Pieces per package 1
Denomination packing units Pcs.
Back to topStandards and regulations
Flammability rating according to UL 94 V0
Back to topClassifications
eCl@ss
eCl@ss 5.1 27180506
eCl@ss 6.0 27180800
eCl@ss 7.0 27182702
eCl@ss 8.0 27182702
eCl@ss 9.0 27182702
Back to topETIM
ETIM 5.0 EC001031
ETIM 6.0 EC001031
ETIM 7.0 EC001031
Back to top

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS CCD 5015 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.