INDUSTRIAL COMPONENT DATA

UCS CCD 7035 2203479 PHOENIX CONTACT Corner inlay

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS CCD 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS CCD 7035
Catalog number	2203479
Category	Extruded profile modular housing
Minimum order	1 Pcs
Document ID	EO-11A6EA8FBE
Generated	2026-11-19

Product Overview

Corner inlay
Angular inserts for UCS housings with integrated threaded mandrel; Material: Polyamide; Colour: light grey, similar to RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2203479
Packing unit 1 pc
GTIN 4055626403465
Weight per Piece (excluding packing) 11.080 g
Custom tariff number 85389099
Country of origin DE (Germany)
Item properties
Type UCS CCD 7035
Order No. 2203479
Housing type Universal housings
Measurements
Width [w] 16.2 mm
Height [h] 16.2 mm

Depth [d] 27.05 mm
Material specifications
Color (RAL) light gray (7035)
Insulating material PA
CTI according to IEC 60112 0
Flammability rating according to UL 94 V0
Housing material PA
Ambient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)
PCB data
Number of PCB holders 1
Note on PCB holders This product is prepared for a printed-circuit board. Additional printed-circuit boards can be mounted using adhesive pads (accessories).
PCB thickness 0.8 mm ... 3 mm
Type of PCB mount Bolt mounting
Note on mounting
Tightening torque / rotational speed Screw connection between housing halves: 1.2 Nm-1.4 Nm / 500 rpm-1000 rpm
Mounting of PCB on corner feeder: 0.4 Nm-0.5 Nm / 500 rpm-1000 rpm
Drive form screw head Mounting the PCB: Slotted Torx®(T7)
Packaging information
Pieces per package 1
Denomination packing units Pcs.
Standards and regulations
Flammability rating according to UL 94 V0
Classifications
eCl@ss 5.127180506eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702
ETIM 5.0EC001031ETIM 6.0EC00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS CCD 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.