INDUSTRIAL COMPONENT DATA

UCS DIN 145-H 7035 2203840 PHOENIX CONTACT DIN rail adapter for mounting one UCS 145-125-H housing (long sid..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS DIN 145-H 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS DIN 145-H 7035
Catalog number	2203840
Category	DIN-rail adapter
Minimum order	1 Pcs
Document ID	EO-6BA42EC955
Generated	2026-11-19

Product Overview

DIN rail adapter for mounting one UCS 145-125-H housing (long side) or UCS 195-145-H housing (short side) onto an NS 35 DIN rail; will be set into the housing instead of a UCS SW 145 side wall; material: polycarbonate; color: light gray, similar to RAL 7035
Rail adapter for mounting a UCS 145-125-H (long side) or UCS 195-145-H (short side) housing on a DIN NS 35 rail, it is placed in the housing instead of a UCS SW 145 sidewall, material: polycarbonate, color: light gray similar to RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2203840
Packing unit 1 pc
GTIN 4055626540320
Weight per Piece (excluding packing) 0.000 g
Custom tariff number 39269097
Country of origin DE (Germany)
Item properties
Material specifications
General information
Standards and regulations

Measurements
Ambient conditions
Packaging information
Classifications
Item properties
Type UCS DIN 145-H 7035
Order No. 2203840
Housing type Universal housings
Type high
Back to topMeasurements
Width [w] 59.4 mm
Height [h] 116 mm
Depth [d] 16.9 mm
Back to topMaterial specifications
Color (RAL) light gray (7035)
Insulating material PC
Flammability rating according to UL 94 V0
Housing material PC
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)
Back to topGeneral information
Note Observe the notes in the data sheet.
Back to topPackaging information
Pieces per package 1
Denomination packing units Pcs.
Back to topStandards and regulations
Flammability rating according to UL 94 V0
Back to topClassifications
eCl@ss
eCl@ss 5.0 27370400
eCl@ss 5.1 27370400
eCl@ss 6.0 27370400
eCl@ss 7.0 27370419
eCl@ss 8.0 27370419
eCl@ss 9.0 27370419
Back to topETIM
ETIM 5.0 EC001024
ETIM 6.0 EC001024
ETIM 7.0 EC001024
Back to top

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS DIN 145-H 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.