INDUSTRIAL COMPONENT DATA

UCS PED 5018 2203394 PHOENIX CONTACT Stand for mounting the UCS housing, height: 47 mm material: polyamide c..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS PED 5018



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS PED 5018
Catalog number	2203394
Category	Extruded profile modular housing
Minimum order	1 Pcs
Document ID	EO-AB6AF7E9BB
Generated	2026-11-19

Product Overview

Stand for mounting the UCS housing, height: 47 mm; material: polyamide; color: turquoise blue, similar to RAL 5018; wall mounting option is integrated, snaps into the screw holes of the housing
Foot for placing UCS housings, height: 47 mm, material: polyamide, color: turquoise, similar to RAL 5018, integrated wall mounting option, fits into the threaded holes of the case

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.
General The UCS PED... stand has drill holes that are also suitable for wall mounting.
Recommended screws for wall mounting: S5 dowel, screw ø 4.0 mm.
Product propertiesProduct type Mounting material
Housing type Universal housings
Housing series UCS
Ventilation openings present no
Data management status
Article revision 02
DimensionsWidth 90 mm

Height 37.5 mm
Depth 19.2 mm
Diameter mounting hole 4 mm
Material specificationsColor (Housing) turquoise green (RAL 5018)
Flammability rating according to UL 94 V0
CTI according to IEC 60112 600
Insulating material PA
Housing material Polyamide
Surface characteristics untreated
Environmental and real-life conditionsAmbient conditions
Max. IP code to attain IP40
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Relative humidity (storage/transport) 80 %
MountingMounting type Snap in
Mounting position Wall mounting
Packaging specificationsType of packaging PE bag

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS PED 5018 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.