INDUSTRIAL COMPONENT DATA

# UCS WM-B 5018 2203391 PHOENIX CONTACT Adapter for mounting the UCS housing on the wall, material: polyamide,..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS WM-B 5018**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | UCS WM-B 5018 |
| Catalog number | 2203391 |
| Category | Extruded profile modular housing |
| Minimum order | 1 Pcs |
| Document ID | EO-4579BA8212 |
| Generated | 2026-11-18 |

## Product Overview

Adapter for mounting the UCS housing on the wall, material: polyamide, color: turquoise similar to RAL 5018, used instead of UCS CC corner insert. Only used in conjunction with UCS GD 9005 adhesive pad
The adapter for attaching the UCS enclosure to the wall with polyamide material and turquoise blue color, similar to RAL 5018, is used instead of the UCS CC angular insert. Use only in combination with the UCS GD 9005 adhesive backing

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Housing (HS) |

## Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.
Product propertiesProduct type Mounting material
Housing type Universal housings
Housing series UCS
Ventilation openings present no
Data management status
Article revision 00
DimensionsWidth 29.6 mm
Height 29.6 mm
Depth 30.95 mm
Diameter mounting hole 4 mm
Material specificationsColor (Housing) turquoise green (RAL 5018)

Flammability rating according to UL 94 V0
CTI according to IEC 60112 600
Insulating material PA
Housing material Polyamide
Surface characteristics untreated
Environmental and real-life conditionsVibration test
Specification IEC 60068-2-6:2007-12
Frequency 10 - 150 - 10 Hz
Sweep speed 1 octave/min
Amplitude 0.15 mm (10 Hz ... 58.1 Hz)
Acceleration 2g (58.1 Hz ... 150 Hz)
Test duration per axis 2.5 h
Test directions X-, Y- and Z-axis
Glow-wire test
Specification IEC 60695-2-11:2014-02
Temperature 850 °C
Time of exposure 30 s
Thermal stability / ball thrust test
Specification IEC 60695-10-2:2014-02
Temperature 125 °C
Test duration 1 h
Force 20 N
Mechanical strength / tumbling barrel
Specification IEC 60068-2-31:2008-05
Height of fall 50 cm
Frequency 50
Shocks
Specification IEC 60068-2-27:2008-02
Pulse shape Half-sine
Acceleration 15g
Shock duration 11 ms
Number of shocks per direction 3
Test directions X-, Y- and Z-axis (pos. and neg.)
Test for substances that would hinder coating with paint or varnish
Specification VW PV 3.10.7:2005-02
Result Test passed
Degree of prot...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS WM-B 5018 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.