INDUSTRIAL COMPONENT DATA

UCS WM-B 7035 2203718 PHOENIX CONTACT Adapter for mounting the UCS housing on the wall, material: polyamide,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS WM-B 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS WM-B 7035
Catalog number	2203718
Category	Extruded profile modular housing
Minimum order	1 Pcs
Document ID	EO-F2B3D7CDB0
Generated	2026-11-19

Product Overview

Adapter for mounting the UCS housing on the wall, material: polyamide, color: light gray similar to RAL 7035, used instead of UCS CC corner insert; only used in conjunction with UCS GD 9005 adhesive pad
The adapter for attaching the UCS box to the wall with polyamide material and light grey colour, similar to RAL 7035, is used in place of the UCS CC angle insert, only in combination with the UCS GD 9005 adhesive backing

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2203718
Packing unit 1 pc
GTIN 4055626436593
Weight per Piece (excluding packing) 20.000 g
Custom tariff number 39269097
Country of origin DE (Germany)
Item properties
Material specifications
Packaging information
Classifications
Measurements

Ambient conditions
Standards and regulations
Item properties
Type UCS WM-B 7035
Order No. 2203718
Housing type Universal housings
Back to topMeasurements
Width [w] 16 mm
Height [h] 25.95 mm
Depth [d] 21 mm
Diameter mounting hole 4 mm
Back to topMaterial specifications
Color (RAL) light gray (7035)
Insulating material PA
Flammability rating according to UL 94 V0
Housing material PA
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)
Back to topPackaging information
Pieces per package 1
Denomination packing units Pcs.
Back to topStandards and regulations
Flammability rating according to UL 94 V0
Back to topClassifications
eCl@ss
eCl@ss 5.1 27180506
eCl@ss 6.0 27180800
eCl@ss 7.0 27182702
eCl@ss 8.0 27182702
eCl@ss 9.0 27182702
Back to topETIM
ETIM 5.0 EC001031
ETIM 6.0 EC001031
ETIM 7.0 EC001031
Back to top

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS WM-B 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.