INDUSTRIAL COMPONENT DATA

UCT-EM (10X8) YE CUS 8191837 PHOENIX CONTACT Label to fit, Mat, yellow, labeled according to customer requir..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCT-EM (10X8) YE CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCT-EM (10X8) YE CUS
Catalog number	8191837
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-EFC8CBD6AB
Generated	2026-11-19

Product Overview

Label to fit, Mat, yellow, labeled according to customer requirements, mounting Type: snap in media for signage, useful Surface area: 10 x 8 mm
Fitting sign, Mat, yellow, labelled according to customer specifications, mounting type: fit on signage support, useful surface: 10x8mm, Number of individual indexes: 36

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Data commercial
Key order Eight million one hundred ninety one thousand eight hundred thirty seven
Packing unit 1 pcs
Key selling BG8148 -
Note Manufacturing under the order. (No refund)
EAN Four trillion fifty five billion six hundred twenty six million one hundred thirteen thousand seven hundred eighty four
Unit weight (excluding packaging) 9,990 g
Tariff number tariff Forty nine million one hundred nineteen thousand nine hundred
Country of origin (Germany)
Measures
Length (b) 8 mm
Width (a) 10 mm

Environmental conditions
Room temperature (service) -40 °C ... 120 °C
Overview
Color yellow
Substances contained contains no silicones or halogens
Class of flammability according to UL 94 V0
Material PC
RoHS compliant Yes
Resistance to the cleaned DIN EN 61010-1 (VDE 0411-1)
Number of individual indexes Thirty six
Number of individual labels per line Six
Test of harmful substances for wetting varnish VW PV 3.10.7:2005-02
Result Test approved
Resistance to adverse weather conditions specification of the test IN accordance with DIN en ISO 4892-2:2013-06
Duration of test (hours) 96 h
Result test of resistance to cleaning Test approved
Salt fog specification test DIN EN 60068-2-11:2000-02
Duration of the test 96 h
The result of the test of fog output Test approved
Resistance to the cleaning of the labels of specification test DIN EN 61010-1 (VDE 0411-1):2002-08
Result Test approved
Mounting type, marking fit in support for signaling
Result Test approved
Oxygen index (en ISO 4589-2) 3...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCT-EM (10X8) YE CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.