INDUSTRIAL COMPONENT DATA

UCT-WMS 3,2 (12X4) BU CUS 0830207 PHOENIX CONTACT Conductor marking collar

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCT-WMS 3,2 (12X4) BU CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCT-WMS 3,2 (12X4) BU CUS
Catalog number	0830207
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-FA3BBB97AF
Generated	2026-11-18

Product Overview

Conductor marking collar
Conductor identification sleeve, available: by mats, blue, labeled according to customer's instructions, mounting class: slip, for terminal width: 5.2 mm, cable diameter range: 1.5 ... 3.2 mm, usable surface: 12 x 4 mm, Number of individual indices: 55
Conductor marking collar, Sheet, can be ordered: by sheet, blue, labeled according to customer specifications, mounting type: slide-on, for terminal block width: 5.2 mm, cable diameter range: 1.5 ... 3.2 mm, Number of individual labels: 55

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Technical dataProduct propertiesProduct type Labeled conductor marker
Pitch 5.2 mm
Type Card form
Data management status
Article revision 01
Marking
Number of individual labels 55
Number of individual labels per row 11
Identification technology Thermal transfer for sheets and cards
MountingMounting type slide-on

Material specificationsColor blue (RAL 5015)
Material PC
Flammability rating according to UL 94 V0
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Components free from silicone and halogen
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
Test for substances that would hinder coating with paint or varnish
Result Test passed
Scratch test for the determining scratch resistance
Specification EN ISO 1518-1:2023 (following)
Requirements >= 5 N
Result Test passed
Tesafilm test
Specification DIN EN ISO 2409:2013 (following)
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Temperature resistance
Specification ANSI/UL 969-2018:03 (following)
Test duration 240 h
Rating 100 °C (121 °C) Test passed
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-01):2020-03
DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl
[CAS No. 67-63-0] Test passed
n-Hexane
[CAS No. 110-54-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCT-WMS 3,2 (12X4) BU CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.