INDUSTRIAL COMPONENT DATA

UCT6M-TM 6 CUS 0830763 PHOENIX CONTACT Marker for terminal blocks from the SNK series from ABB

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCT6M-TM 6 CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCT6M-TM 6 CUS
Catalog number	0830763
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-1DBE59724E
Generated	2026-11-19

Product Overview

Marker for terminal blocks from the SNK series from ABB
Markers for ABB SNK series terminal blocks, available: by mats, white, labeled according to customer specifications, mounting class: fit in high index slot, for terminal width: 6 mm, useful surface: 4.85x11.3mm, Number of individual indexes: 50

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 0830763
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 135 (C-5-2013)
GTIN 4046356745796
Weight per Piece (excluding packing) 11.000 g
Custom tariff number 49119900
Country of origin DE (Germany)
Dimensions
Length (b) 11.9 mm
Width (a) 5.45 mm

Height (c) 2.7 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Color white
Type high
Components free from silicone, halogen, and cadmium
Flammability rating according to UL 94 V0
Material PC
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 50
Number of individual labels per row 10
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type snap into tall marker groove
Result Test passed
Oxygen index (DIN EN ISO 4589-2) 32.4 %
R22 HL 1 - HL 3
R23 HL 1 - HL 3
R24 HL 1 - HL 3
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Flammability rating accord...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCT6M-TM 6 CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.