INDUSTRIAL COMPONENT DATA

# UCT6M-TM 8 CUS 0830764 PHOENIX CONTACT Marker for terminal blocks from the SNK series from ABB

**Brand: PHOENIX CONTACT | Manufacturer Part Number: UCT6M-TM 8 CUS**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | UCT6M-TM 8 CUS |
| Catalog number | 0830764 |
| Category | Labelling for terminal block |
| Minimum order | 1 Pcs |
| Document ID | EO-C56A6D104A |
| Generated | 2026-11-19 |

## Product Overview

Marker for terminal blocks from the SNK series from ABB
ABB SNK series terminal block markers, available: by mats, white, labelled according to customer specifications, mounting class: fit into high index slot, for terminal width: 8 mm, usable surface: 6.85 x 11.3 mm, Number of individual indexes: 35

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > CABINET add-on |

## Additional Product Information

Key Commercial Data
Orderkey 0830764
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 135 (C-5-2013)
GTIN 4046356745802
Weight per Piece (excluding packing) 10.600 g
Custom tariff number 49119900
Country of origin DE (Germany)
Dimensions
Length (b) 11.9 mm
Width (a) 7.45 mm
Height (c) 2.7 mm

Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Color white
Type high
Components free from silicone, halogen, and cadmium
Flammability rating according to UL 94 V0
Material PC
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 35
Number of individual labels per row 7
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type snap into tall marker groove
Result Test passed
Oxygen index (DIN EN ISO 4589-2) 32.4 %
R22 HL 1 - HL 3
R23 HL 1 - HL 3
R24 HL 1 - HL 3
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Flammability rating accordi...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCT6M-TM 8 CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.



Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.