INDUSTRIAL COMPONENT DATA

UK 10-DREHSI-EX (5X20) 3073953 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 10-DREHSI-EX (5X20)



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 10-DREHSI-EX (5X20)
Catalog number	3073953
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-D5F501F6CA
Generated	2026-11-19

Product Overview

Fuse modular terminal block

Fuse terminal block, for fuse cartridge G, cross-section: 0.5 - 16 mm², AWG: 24 - 6, width: 12 mm, colour: Black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3073953
Packing unit 50 pc
Minimum order quantity 50 pc
GTIN 4046356343121
Weight per Piece (excluding packing) 33.800 g
Custom tariff number 85369095
Country of origin PL (Poland)
General
Number of levels 1
Number of connections 2
Nominal cross section 16 mm²
Color black
Insulating material PA

Flammability rating according to UL 94 V2
Maximum power dissipation for nominal condition 2.43 W
Fuse G / 5 x 20
Fuse type Glass / ceramics / ...
Rated surge voltage 4 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-3
Maximum load current 10 A
Nominal current IN 10 A
Nominal voltage UN 500 V (As a fuse terminal block)
800 V (As a disconnect terminal block)
Open side panel No
Dimensions
Width 12 mm
Length 62 mm
Height NS 35/7,5 57.2 mm
Height NS 35/15 64.7 mm
Height NS 32 62.2 mm
Connection data
Conductor cross section solid min. 0.5 mm²
Conductor cross section solid max. 16 mm²
Conductor cross section flexible min. 0.5 mm²
Conductor cross section flexible max. 16 mm²
Conductor cross section AWG min. 20
Conductor cross section AWG max. 6
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 10 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 10 mm²
Cross section with insertion...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 10-DREHSI-EX (5X20) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.