

INDUSTRIAL COMPONENT DATA

UK 10,3-CC HESILED N 72 3048690 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 10,3-CC HESILED N 72



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 10,3-CC HESILED N 72
Catalog number	3048690
Category	Fuse terminal block
Minimum order	12 Pcs
Document ID	EO-BC6882BB77
Generated	2026-09-22

Product Overview

Fuse modular terminal block

Rail terminal for fuse, fuse type: Glass/ceramic/..., fuse type: DC class, nominal voltage: 72 V, nominal current: 32 A, connection type: Screw connection, Sizing cross-section: 25 mm², cross-section: 1.5 mm²- 25 mm², mounting class: NS 35/7.5, NS 35/15, color: black

Fuse modular terminal block, fuse type: Glass / ceramics / ..., fuse type: Class CC, nom. voltage: 72 V, nominal current: 30 A, connection method: Screw connection, Rated cross section: 25 mm², cross section: 1.5 mm²- 25 mm², mounting type: NS 35/7,5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataNotesTrade restriction

CE note The products are offered exclusively for export outside the EU and the European Economic Area.

Product propertiesProduct type Fuse terminal block

Number of connections 2

Number of rows 1

Data management status

Article revision 03

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical properties Fuse type Glass / ceramics / ...

Rated surge voltage 6 kV

Maximum power dissipation for nominal condition 4 W

Fuse Class CC

LED voltage range 12 V ... 72 V

Input data LED voltage range 12 V ... 72 V

Connection data Number of connections per level 2

Nominal cross section 25 mm²

Screw thread M5

Tightening torque 2 ... 2.5 Nm

Stripping length 11 mm

Internal cylindrical gage B6

Conductor cross section rigid 1.5 mm² ... 25 mm²

Cross section AWG 14 ... 4 (converted acc. to IEC)

Conductor cross section flexible 1.5 mm² ... 25 mm²

Conductor cross section, flexible [AWG] 14 ... 4 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 1.5 mm² ... 16 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 1.5 mm² ... 16 mm²

Cross-section with insertion bridge, rigid 10 mm²

Cross-section with insertion bridge, flexible 10 mm²

2 conductors with same cross section, solid 1.5 mm² ... 4 mm²

2 conductors with same cross section, flexible 1.5 mm² ... 4 mm²

2 conductors with same cross section, flexible, with ferrule without plastic sleeve 1.5 mm² ... 4 mm²

2 conductors with the same cro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 10,3-CC HESILED N 72 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.