

INDUSTRIAL COMPONENT DATA

UK 10,3-HESILED N 72 3048661 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 10,3-HESILED N 72



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 10,3-HESILED N 72
Catalog number	3048661
Category	Fuse terminal block
Minimum order	12 Pcs
Document ID	EO-17DA10C844
Generated	2026-09-20

Product Overview

Fuse modular terminal block

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: Midget / 10.3 x 38, nominal voltage: 72 V, nominal current: 32 A, connection type: Screw connection, Sizing cross-section: 16 mm², cross-section: 1.5 mm²- 25 mm², mounting class: NS 35/7.5, NS 35/15, color: black

Fuse modular terminal block, fuse type: Glass / ceramics / ..., fuse type: Midget / 10.3 x 38, nom. voltage: 72 V, nominal current: 32 A, connection method: Screw connection, Rated cross section: 16 mm², cross section: 1.5 mm²- 25 mm², mounting type: NS 35/7,5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Fuse terminal block

Number of connections 2

Number of rows 1

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical propertiesFuse type Glass / ceramics / ...

Rated surge voltage 6 kV

Maximum power dissipation for nominal condition 3 W

Fuse Midget / 10.3 x 38

LED voltage range 12 V AC ... 72 V AC (The voltage is determined by the fuse or selected LED display)

Input dataLED voltage range 12 V AC ... 72 V AC (The voltage is determined by the fuse or selected LED display)

Connection dataNumber of connections per level 2

Nominal cross section 16 mm²

Level 1 above 1 below 1

Screw thread M5

Tightening torque 2 ... 2.5 Nm

Stripping length 11 mm

Internal cylindrical gage A7

Connection in acc. with standard IEC 60947-1 / -3

Conductor cross section rigid 1.5 mm² ... 25 mm²

Cross section AWG 14 ... 4 (converted acc. to IEC)

Conductor cross section flexible 1.5 mm² ... 16 mm²

Conductor cross section, flexible [AWG] 14 ... 6 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 1.5 mm² ... 16 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 1.5 mm² ... 16 mm²

Cross-section with insertion bridge, rigid 10 mm²

Cross-section with insertion bridge, flexible 10 mm²

2 conductors with same cross section, solid 1.5 mm² ... 4 mm²

2 conductors with same cross section, flexible 1.5 mm² ... 4 mm²

2 conductors with same cross section, flexible, with ferrule without plastic....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 10,3-HESILED N 72 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.