INDUSTRIAL COMPONENT DATA

UK 2,5 B BU 3001048 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 2,5 B BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 2,5 B BU
Catalog number	3001048
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-63CA7EC1B3
Generated	2026-11-19

Product Overview

Feed-through terminal block
Feed-through terminal, nominal voltage: 690 V, nominal current: 24 A, number of connections: 2, connection type: Screw connection, cross-section: 0.2 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3001048
Packing unit 50 pc
Minimum order quantity 50 pc
GTIN 4017918089795
Weight per Piece (excluding packing) 7.000 g
Custom tariff number 85369010
Country of origin CN (China)
General
Number of levels 1
Number of connections 2
Potentials 1
Color blue

Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Nominal current IN 24 A
Nominal voltage UN 690 V
Open side panel Yes
Shock protection test specification IEC 60529:2001-02
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 9.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.2 mm² / 0.2 kg
2.5 mm² / 0.7 kg
4 mm² / 0.9 kg
Tensile test result Test passed
Conductor cross section tensile test 0.2 mm²
Tractive force setpoint 10 N
Conductor cross section tensile test 2.5 mm²
Tractive force setpoint 50 N
Conductor cross section tensile test 4 mm²
Tractive force setpoint 60 N
Result of tight fit on support Test passed
Tight fit on carrier NS 32/NS 35
Setpoint 1 N
Result of voltage-drop test Test passed
Req...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 2,5 B BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.