INDUSTRIAL COMPONENT DATA

UK 35 TEILBESTUECKT 0711399 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 35 TEILBESTUECKT



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 35 TEILBESTUECKT
Catalog number	0711399
Category	Feed-through terminal block
Minimum order	25 Pcs
Document ID	EO-CB5C728601
Generated	2026-11-19

Product Overview

Feed-through terminal block
Feed-through terminal, The terminal block has only one screw, nominal voltage: 1000 V, nominal current: 150 A, connection type: Screw connection, number of connections: 1, cross-section: 0.75 mm² - 50 mm², AWG: 18 - 1/0, width: 16 mm, color: gray, mounting class: NS 35/7.5, NS 35/15, NS 32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 0711399
Packing unit 25 pc
Minimum order quantity 25 pc
Note Made to Order (non-returnable)
GTIN 4017918320614
Weight per Piece (excluding packing) 48.960 g
Custom tariff number 85369010
Country of origin DE (Germany)
General
Number of levels 1
Number of connections 1

Potentials 1
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum load current 150 A (with 50 mm² conductor cross section)
Nominal current IN 150 A
Nominal voltage UN 1000 V
Open side panel No
Dimensions
Width 16 mm
Length 50 mm
Height NS 35/7,5 62 mm
Height NS 35/15 69.5 mm
Height NS 32 67 mm
Connection data
Connection method Screw connection
Connection in acc. with standard IEC 60947-7-1
Conductor cross section solid min. 0.75 mm²
Conductor cross section solid max. 50 mm²
Conductor cross section AWG min. 18
Conductor cross section AWG max. 1/0
Conductor cross section flexible min. 0.75 mm²
Conductor cross section flexible max. 35 mm²
Min. AWG conductor cross section, flexible 18
Max. AWG conductor cross section, flexible 2
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.75 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 35 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.75 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 35 mm²
2 conduct...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 35 TEILBESTUECKT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.