

INDUSTRIAL COMPONENT DATA

UK 5-HESILED 60 3004139 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 5-HESILED 60



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 5-HESILED 60
Catalog number	3004139
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-D2139038D1
Generated	2026-09-22

Product Overview

Fuse modular terminal block

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, nominal voltage: 60 V, nominal current: 6.3 A, connection type: Screw connection, Sizing cross-section: 1 mm², cross-section: 0.2 mm²- 4 mm², mounting class: NS 35/7.5, NS 35/15, NS 32, colour: black

Fuse modular terminal block, fuse type: Glass / ceramics / ..., fuse type: G / 5 x 20, nom. voltage: 60 V, nominal current: 6.3 A, connection method: Screw connection, Rated cross section: 1 mm², cross section: 0.2 mm²- 4 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataNotesNote regarding marking For terminal marking, please use marking material with 8.2 mm pitch.

Note regarding marking For lever marking, please use marking material with 6.2 mm pitch.

Product propertiesProduct type Fuse terminal block

Number of connections 2

Number of rows 1

Potentials 1

Data management status

Article revision 09

Insulation characteristics

Overvoltage category III
Degree of pollution 3
Electrical properties Fuse type Glass / ceramics / ...
Rated surge voltage 8 kV
Maximum power dissipation for nominal condition 1.02 W
Fuse G / 5 x 20
LED voltage range 60 V AC/DC
Input data LED voltage range 60 V AC/DC
Connection data Number of connections per level 2
Nominal cross section 4 mm²
Level 1 above 1 below 1
Screw thread M3
Tightening torque 0.6 ... 0.8 Nm
Stripping length 8 mm
Internal cylindrical gage A4
Connection in acc. with standard IEC 60947-7-3
Conductor cross section rigid 0.2 mm² ... 4 mm²
Cross section AWG 24 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0.2 mm² ... 4 mm²
Conductor cross section, flexible [AWG] 24 ... 12 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.25 mm² ... 4 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.25 mm² ... 4 mm²
Cross-section with insertion bridge, rigid 4 mm²
Cross-section with insertion bridge, flexible 4 mm²
2 conductors with same cross section, solid 0.2 mm² ... 1.5 mm²
2 conductors with same cross section, flexible 0.2 mm²...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 5-HESILED 60 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.