

## INDUSTRIAL COMPONENT DATA

# UK 5-MTK-P/P RD 3048292 PHOENIX CONTACT Knife disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 5-MTK-P/P RD



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | PHOENIX CONTACT                   |
| MPN / Reference | UK 5-MTK-P/P RD                   |
| Catalog number  | 3048292                           |
| Category        | (Knife) disconnect terminal block |
| Minimum order   | 50 Pcs                            |
| Document ID     | EO-06417D0A19                     |
| Generated       | 2026-09-22                        |

## Product Overview

Knife disconnect terminal block

Blade interruptible terminal block, with threaded sockets for test sockets to accommodate test pins, nominal voltage: 500 V, nominal current: 16 A, 1st floor, connection type: Screw connection, Sizing section: 2.5 mm<sup>2</sup>, section: 0.2 mm<sup>2</sup> - 6 mm<sup>2</sup>, mounting: NS 32, NS 35/7.5, NS 35/15, color: red

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > Modular TBs |
|--------------|-------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 3048292

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4017918949181

Weight per Piece (excluding packing) 12.440 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 2

Nominal cross section 4 mm<sup>2</sup>  
Color red  
Insulating material PA  
Flammability rating according to UL 94 V0  
Rated surge voltage 6 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Nominal current I<sub>N</sub> 16 A  
Maximum load current 16 A (with 4 mm<sup>2</sup> conductor cross section)  
Nominal voltage U<sub>N</sub> 500 V  
Open side panel No  
Number of positions 1  
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11  
Back of the hand protection guaranteed  
Finger protection guaranteed  
Result of surge voltage test Test passed  
Surge voltage test setpoint 7.3 kV  
Result of power-frequency withstand voltage test Test passed  
Power frequency withstand voltage setpoint 1.89 kV  
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed  
Result of bending test Test passed  
Bending test conductor cross section/weight 0.2 mm<sup>2</sup> / 0.2 kg  
4 mm<sup>2</sup> / 0.9 kg  
6 mm<sup>2</sup> / 1.4 kg  
Tensile test result Test passed  
Conductor cross section tensile test 0.2 mm<sup>2</sup>  
Tractive force setpoint 10 N  
Conductor cross section tensile test 4 mm<sup>2</sup>  
Tractive force setpoint 60 N  
Conductor cross section tensile test 6 mm<sup>2</sup>  
Tractive force setpoint 80 N  
Result of tight fit on support Test pass...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 5-MTK-P/P RD with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.