INDUSTRIAL COMPONENT DATA

UKH 50 1500V 3247400 PHOENIX CONTACT High-current terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UKH 50 1500V



Manufacturer	PHOENIX CONTACT
MPN / Reference	UKH 50 1500V
Catalog number	3247400
Category	Feed-through terminal block
Minimum order	10 Pcs
Document ID	EO-4E55A9DE83
Generated	2026-11-19

Product Overview

High-current terminal block
Current terminal, nominal voltage: 1500 V, nominal current: 150 A, number of connections: 2, connection type: Screw connection, Sizing cross-section: 50 mm², cross-section: 16 mm² - 70 mm², mounting class: NS 35/7.5, NS 35/15, NS 32, NS 35/15-2.3, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3247400
Packing unit 10 pc
Minimum order quantity 10 pc
Catalog page Page 257 (C-1-2017)
GTIN 4055626132945
Weight per Piece (excluding packing) 124.330 g
Custom tariff number 85359000
Country of origin IN (India)
General
Number of levels 1
Number of connections 2

Potentials 1
Nominal cross section 50 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 4.73 W
Maximum load current 150 A (with 50 mm² conductor cross section)
Nominal current IN 150 A
Nominal voltage UN 1500 V
Open side panel No
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UKH 50 1500V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.