INDUSTRIAL COMPONENT DATA

UKK 3-MSTB-5,08 2770888 PHOENIX CONTACT Double-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UKK 3-MSTB-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	UKK 3-MSTB-5,08
Catalog number	2770888
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-4396C79AEC
Generated	2026-11-19

Product Overview

Double-level terminal block
Terminal blocks for double-deck rail with COMBICON plug-in zone, rated current: 12 A, rated voltage: 250 V, cross-section: 0.2 mm² - 4 mm², AWG: 24 - 12, mounting type: NS 35/7.5, NS 35/15, NS 32, pitch dimension: 5.08 mm, width: 5.08, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 2770888
Packing unit 50 pc
Catalog page Page 324 (CL-2005)
GTIN 4017918068110
Weight per Piece (excluding packing) 8.180 g
Custom tariff number 85369010
Country of origin GR (Greece)
General
Number of levels 2
Number of connections 4
Color gray

Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 4 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Nominal current IN 10 A
Maximum load current 12 A (with 4 mm² conductor cross section)
Nominal voltage UN 250 V
Open side panel Yes
Number of positions 1
Connection data
Connection labeling 1st and 2nd level connection left
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 4 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 1.5 mm²
2 conductors with same cross section, solid min. 0.2 mm²
2 conductors with same cross section, solid max. 1.5 mm²
2 conductors with same cross section, stranded min. 0.2 mm²
2 conductors with same cross section, stranded max. 1 mm²
2 conductors with same cross...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UKK 3-MSTB-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.