INDUSTRIAL COMPONENT DATA

UKK 3-MSTB-5,08 AU 32L 2770969 PHOENIX CONTACT Double-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UKK 3-MSTB-5,08 AU 32L



Manufacturer	PHOENIX CONTACT
MPN / Reference	UKK 3-MSTB-5,08 AU 32L
Catalog number	2770969
Category	Feed-through terminal block
Minimum order	5 Pcs
Document ID	EO-9212D60DD1
Generated	2026-11-19

Product Overview

Double-level terminal block
Double-level terminal block, 32 locked poles, nominal voltage: 250 V, nominal current: 10 A, number of connections: 128, number of poles: 32, connection type: Screw connection / plug-in connection, 1. And 2nd floor, connection on the left, cross-section: 0.2 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, NS 32, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 2770969
Packing unit 5 pc
Note Made to Order (non-returnable)
GTIN 4017918243357
Weight per Piece (excluding packing) 116.400 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of levels 2
Number of connections 128
Color gray

Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 4 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection method Screw connection
Maximum load current 12 A (with 4 mm² conductor cross section)
Nominal current IN 10 A
Nominal voltage UN 250 V
Open side panel Yes
Dimensions
Width 88.9 mm
Length 50 mm
Pitch 5.08 mm
Height NS 35/7,5 53.5 mm
End cover width 2.5 mm
Connection data
Connection method Screw connection
Screw thread M3
Tightening torque, min 0.5 Nm
Tightening torque max 0.6 Nm
Stripping length 8 mm
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 4 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Min. AWG conductor cross section, flexible 24
Max. AWG conductor cross section, flexible 14
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule wit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UKK 3-MSTB-5,08 AU 32L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.