INDUSTRIAL COMPONENT DATA

UKK 3-MSTB-5,08-PE 1876615 PHOENIX CONTACT Double-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UKK 3-MSTB-5,08-PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	UKK 3-MSTB-5,08-PE
Catalog number	1876615
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-E2B2F3C837
Generated	2026-11-19

Product Overview

Double-level terminal block
Double-level terminal block, number of connections: 4, number of poles: 1, connection type: Screw connection / plug-in connection, cross-section: 0.2 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, NS 32, color: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 1876615
Packing unit 50 pc
Catalog page Page 325 (CL-2005)
GTIN 4017918134082
Weight per Piece (excluding packing) 11.500 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of levels 2
Number of connections 4
Color green-yellow
Insulating material PA

Flammability rating according to UL 94 V2
Rated surge voltage 4 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Nominal current IN 250 A
Nominal voltage UN 1000 V
Open side panel Yes
Number of positions 1
Connection data
Connection labeling 2nd level connection left
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 4 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 1.5 mm²
Connection method Screw connection
Stripping length 8 mm
Internal cylindrical gage A3
Screw thread M3
Tightening torque, min 0.5 Nm
Tightening torque max 0.6 Nm
Standards and Regulations
Connection in acc. with standard CUL
Flammability rating according to UL 94 V2
Environmental Product Compliance
REACh SVHC Lead 7439-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UKK 3-MSTB-5,08-PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.