

INDUSTRIAL COMPONENT DATA

UKK 5-HESILED 24 (5X20) 1MA 3049000 PHOENIX CONTACT

Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UKK 5-HESILED 24 (5X20) 1MA



Manufacturer	PHOENIX CONTACT
MPN / Reference	UKK 5-HESILED 24 (5X20) 1MA
Catalog number	3049000
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-140F61F6FB
Generated	2026-09-21

Product Overview

Fuse modular terminal block

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, nominal voltage: 24 V, nominal current: 6.3 A, connection type: Screw connection, cross-section: 0.2 mm²- 4 mm², sizing cross-section: 1.5 mm², mounting class: NS 35/7.5, NS 35/15, NS 32, colour: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3049000

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356090858

Weight per Piece (excluding packing) 35.340 g

Custom tariff number 85369095

Country of origin PL (Poland)

General

Note For terminal marking, please use marking material with 8.2 mm pitch.

For lever marking, please use flat marking material with 8.2 mm pitch.

Number of levels 2
Number of connections 4
Nominal cross section 4 mm²
Color black
Insulating material PA
Flammability rating according to UL 94 V0
Maximum power dissipation for nominal condition 1.02 W (the value is multiplied when connecting multiple levels)
Fuse G / 5 x 20
Fuse type Glass / ceramics / ...
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-3
Nominal current I_N 6.3 A
Nominal voltage U_N 24 V
Maximum load current (upper level) 10 A
Nominal current I_N(upper level) 10 A
Nominal voltage U_N 400 V
Open side panel No
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific op...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UKK 5-HESILED 24 (5X20) 1MA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.