INDUSTRIAL COMPONENT DATA

UM-2KS50/4FLK14/YCS 2311166 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-2KS50/4FLK14/YCS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-2KS50/4FLK14/YCS
Catalog number	2311166
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-1D38EA5B6D
Generated	2026-11-18

Product Overview

Passive module
32-channel digital input/output module with redundant voltage power. Suitable for Yokogawa ADV 151, ADV 161, ADV 551 and ADV 561 cards.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2311166
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4046356159739
Weight per Piece (excluding packing) 231.600 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Width 128 mm
Height 78 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Max. perm. operating voltage 24 V DC ±10 %
Max. perm. current (per branch) 1 A
Mounting position any
Connection data for connection 1
Connection name Field level
Connection method IDC/FLK pin strip
Number of connections 4
Number of positions 14
Connection data for connection 2
Connection name Controller level
Connection method Yokogawa KS-compatible
Torque 0.5 Nm
Number of connections 2
Number of positions 50
Note Usable system cables: Phoenix Contact YUC50, Yokogawa AKB331
Supported controller
Controller YOKOGAWA CS3000 CentumVP
- suitable I/O card ADV151
ADV161
ADV551
ADV561
Controller YOKOGAWA STARDOM
- suitable I/O card NFDV151
NFDV161
NFDV551
NFDV561
Standards and Regulations
Standards/regulations DIN EN 50178
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss 5.127371600eCl@ss 6.027371600eCl@ss 7.027141152eCl@ss 8.027141152eCl@ss 9.027141152
ETIM 5.0EC0027...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-2KS50/4FLK14/YCS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.