
INDUSTRIAL COMPONENT DATA

UM-2KS50RM/32MR/SI/1/551/MT 2968564 PHOENIX CONTACT Active module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-2KS50RM/32MR/SI/1/551/MT



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-2KS50RM/32MR/SI/1/551/MT
Catalog number	2968564
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-19575C21D0
Generated	2026-11-19

Product Overview

Active module
VARIOFACE output module, 32 channels for Yokogawa ADV 551, ADV 561 output functional units.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2968564
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4046356458634
Weight per Piece (excluding packing) 1,459.000 g
Custom tariff number 85364190
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 420 mm
Height 128 mm
Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Input data
Nominal input voltage UN 24 V DC
Input voltage range in reference to UN 0.9 ... 1.1
Typical input current at UN 7 mA (per channel (total current: 1 A))
Output data
Contact type 1 N/O contact
Contact material AgSnO
Maximum switching voltage 250 V AC/DC
Minimum switching voltage 12 V AC/DC
Limiting continuous current 1.2 A (Total current 8 A (per 8 channels))
Min. switching current 100 mA
Interrupting rating (ohmic load) max. 29 W (at 24 V DC)
20 W (at 48 V DC)
18 W (at 60 V DC)
23 W (at 110 V DC)
40 W (at 220 V DC)
300 VA (for 250 V AC)
Output fuse 4 A (per channel)
General
No. of channels 32
Mechanical service life 2x 107cycles
Mounting position any
Assembly instructions In rows with zero spacing
Connection data for connection 1
Connection name Field level
Connection method Screw connection with disconnect knife
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Number of connections 1
Connection data...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-2KS50RM/32MR/SI/1/551/MT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.