
INDUSTRIAL COMPONENT DATA

UM-4SL/SPT/ADR541/CS 2968522 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-4SL/SPT/ADR541/CS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-4SL/SPT/ADR541/CS
Catalog number	2968522
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-22B58688D9
Generated	2026-11-19

Product Overview

Passive module
Interconnect module for coupling the field side by means of a spring connection to the Yokogawa ADR 541 card. Fuse (5 x 20) with fuse fault indication (LED) per channel. AKB 334 system connection for control system.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2968522
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4046356340618
Weight per Piece (excluding packing) 1,015.000 g
Custom tariff number 85369010
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 232.5 mm
Height 126 mm

Depth 104 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Note Voltage monitoring on the module does not work in combination with upstream HESILED fuse terminal blocks with integrated LED display.
Max. perm. operating voltage 24 V DC ±10 %
Max. perm. current (per branch) 630 mA
Max. permissible current (all branches) 6.3 A
Status display Green LED
Mounting position any
Assembly instructions In rows with zero spacing
Connection data for connection 1
Connection name Field level
Connection method Spring-cage connection
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Number of positions 32
Connection data for connection 2
Connection name Controller level
Connection method COMBICON connectors
Number of connections 4
Number of positions 18
Note Yokogawa AKB334-compatible
Supported controller
Controller YOKOGAWA CS3000 CentumVP
- suitable I/O card ADR541
Standards and Regulations
Standards/regulations DIN EN 50178
Rated surge voltage 0.8 kV (basic in...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-4SL/SPT/ADR541/CS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.