INDUSTRIAL COMPONENT DATA

UM- 8 RM-S-G24/21/PLC-MSTB 2311030 PHOENIX CONTACT Active module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-8 RM-S-G24/21/PLC-MSTB

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-8 RM-S-G24/21/PLC-MSTB
Catalog number	2311030
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-80332C9540
Generated	2026-11-18

Product Overview

Active module
Relay module, with 8 miniature relays, each with 1 switched contact, plugged in, for 24 V DC (incl. relay)
Relay module, with 8 miniature relays, one changeover contact each, plugged in, for 24 V DC (incl. relay)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Technical dataNotesNotes on operation For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
Product propertiesProduct type Relay Module
With components yes
Insulation characteristics: Air clearances and creepage distances, input/output
Insulation Reinforced insulation
Overvoltage category III
Pollution degree 2
Insulation characteristics: Air and creepage distances, output/output
Insulation Functional insulation
Overvoltage category II
Pollution degree 2

Electrical propertiesAir clearances and creepage distances, input/output
Rated insulation voltage 260 V
Rated surge voltage 6 kV (1.2/50 us)
Air and creepage distances, output/output
Rated insulation voltage 260 V
Rated surge voltage 2.3 kV (1.2/50 us)
Input dataNominal input voltage UN 24 V DC (±10 %)
Typical input current at UN 200 mA (200 mA supply / <= 20 mA input current per signal)
Output dataSwitching
Contact switching type Single contact, 1 changeover contact
Maximum switching voltage 150 V AC/DC (Maximum switching voltage of 230 V AC: the maximum switching voltage of 230 V is only permitted if the same fuse circuit is used. The outputs are not suitable for switching different outer conductors.)
Limiting continuous current 4 A
Connection dataController level
Connection in acc. with standard IEC 60603-13
C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-8 RM-S-G24/21/PLC-MSTB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.