INDUSTRIAL COMPONENT DATA

UM-ALU 4-100,5 PROFILE 80 1110467 PHOENIX CONTACT Press-drawn section housings, Basic profile, profile width..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-ALU 4-100,5 PROFILE 80



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-ALU 4-100,5 PROFILE 80
Catalog number	1110467
Category	Extruded profile modular housing
Minimum order	50 Pcs
Document ID	EO-5E30421C24
Generated	2026-11-18

Product Overview

Press-drawn section housings, Basic profile, profile width (internal): 100.5 mm, length: 80 mm
Extruded profile housings, Screwed mounting, Basic profile, colour: aluminium colour, profile width (inside): 100.5 mm, profile width (outside): 105 mm, length: 80 mm, depth: 29.4 mm
Press-drawn section housings, Screw mounting, Basic profile, profile width (internal): 100.5 mm, profile width (external): 105 mm, length: 80 mm, depth: 29.4 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Technical dataProduct propertiesProduct type Component housing lower part
Housing type Press-drawn section housings
Housing series UM-ALU
Product family UM-ALU 4-100,5
Type Basic profile
Ventilation openings present no
Data management status
Article revision 00
DimensionsDimensional drawing
Depth 29.4 mm
Depth from top edge of DIN rail 25.5 mm

Length 80 mm
External dimensions
Profile width (external) 105 mm
Internal dimensions
Profile width (internal) 100.5 mm
PCB design
PCB thickness 1.44 mm ... 2 mm
Material specificationsColor (Housing) Aluminum color
Housing material Aluminum
Surface characteristics anodized
Environmental and real-life conditionsAmbient conditions
Max. IP code to attain IP40
Ambient temperature (operation) -40 °C ... 105 °C
PCB dataNumber of PCB holders 2
Type of PCB mount Slot
Thickness of the PCB 1.44 mm ... 2 mm
MountingMounting type Screw mounting
Mounting position parallel to the DIN rail
Packaging specificationsType of packaging packed in cardboard
Outer packaging type Carton

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-ALU 4-100,5 PROFILE 80 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.