INDUSTRIAL COMPONENT DATA

UM-BASIC 72 L13,14CM KMGY 1017444 PHOENIX CONTACT Press-drawn section housings, Basic profile, profile width..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-BASIC 72 L13,14CM KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-BASIC 72 L13,14CM KMGY
Catalog number	1017444
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-6EAE46C9E1
Generated	2026-11-18

Product Overview

Press-drawn section housings, Basic profile, profile width (internal): 72 mm, length: 131.4 mm, color: light gray (7035)
Extruded profile housings, Locking with side elements, locking with foot element, Basic profile, profile width (inside): 72 mm, length: 131.4 mm, depth: 19.8 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1017444
Packing unit 1
GTIN 4055626511740
Custom tariff number 39269097
Product properties
Material specifications
PCB specifications
Packaging specifications
Dimensions
Ambient conditions
General information
Classifications

Product properties
Brief article description Profile
Type UM-BASIC 72 L13,14CM KMGY
Order No. 1017444
Housing type Press-drawn section housings
Type Basic profile
Mounting type Latching with side elements, latching with foot element
Back to topDimensions
Profile PCB width (selectable): 72 mm [UM72]
Depth [d] 19.8 mm
Back to topMaterial specifications
Housing material PVC
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 50 °C
Ambient temperature (assembly) -5 °C ... 50 °C
Ambient temperature (operation) -15 °C ... 50 °C (depending on power dissipation)
Relative humidity (storage/transport) 95 %
Back to topPCB specifications
Mounting position parallel to the DIN rail
Type of PCB mount Insertion/securing with additional elements
Back to topGeneral information
Type of note Assembly instruction:
Note Refer to the data sheet for the range in the download area.
Back to topPackaging specifications
Pieces per package 10
Denomination packing units Pcs.
Back to topClassifications
eCl@ss
eCl@ss 10.0.1 27182701
eCl@ss 8.0 27182701
eCl@ss 9.0 27182701
Back to topETIM
ETIM 5.0 EC002779
ETIM 6.0 EC002779
ETIM 7.0 EC002779
Back to top

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-BASIC 72 L13,14CM KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.