INDUSTRIAL COMPONENT DATA

UM-D25SUB/F/PTS/MSTB/GF-AO 2902086 PHOENIX CONTACT Analog VARIOFACE output module, with COMBICON screw conne..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-D25SUB/F/PTS/MSTB/GF-AO

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-D25SUB/F/PTS/MSTB/GF-AO
Catalog number	2902086
Category	Interface module
Minimum order	10 Pcs
Document ID	EO-48F7413525
Generated	2026-11-19

Product Overview

Analog VARIOFACE output module, with COMBICON screw connection and a 25-pos. D-SUB female connector. The signal path can be interrupted with a disconnect knife.
VARIOFACE analogue output module, with COMBICON screw connection and a 25-pole SUB D connection socket. With a knife separation, the signal track can be interrupted.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Analog VARIOFACE output module, with COMBICON screw connection and a 25-pos. D-SUB female connector. The signal path can be interrupted with a disconnect knife.
Key Commercial Data
Orderkey 2902086
Packing unit 1
GTIN 4046356648578
Custom tariff number 85369010
Dimensions
Width 75 mm
Height 111 mm

Depth 56 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C
Maximum altitude <= 2000 m
Degree of protection IP00
General
Nominal voltage UN 25 V AC/DC
Max. perm. current (per branch) 2 A
Mounting position any
Degree of protection IP00
Connection data
Connection name Field level
Connection method Screw connection
Conductor cross section solid 0.2 mm² ... 2.5 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Connection data 2
Connection name Controller level
Connection method D-SUB socket strip
Number of positions 25
Standards and Regulations
Designation Air clearances and creepage distances
Standards/regulations DIN EN 50178: 1998-04
Rated insulation voltage 50 V
Rated surge voltage 0.5 kV (1.2/50 us)
Insulation Functional insulation
Degree of pollution 2
Overvoltage category II
Environmental Product Compliance
REACh SVHC
Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss
eCl@ss 4.0 27250313
eCl@ss 4.1 27250313
eCl@ss 5.0 27250313
eCl@ss 5.1 27250300
eCl@ss 6.0 27242600
eCl@ss 7.0 27...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-D25SUB/F/PTS/MSTB/GF-AO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.