INDUSTRIAL COMPONENT DATA

UM-D37M/16RSC-24DC/DO/C3/L IMC 2906193 PHOENIX CONTACT Active module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-D37M/16RSC-24DC/DO/C3/L IMC



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-D37M/16RSC-24DC/DO/C3/L IMC
Catalog number	2906193
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-870BCA774D
Generated	2026-11-18

Product Overview

Active module
VARIOFACE module with 16 channels for use with Honeywell® Experion C300-24 V-Digital-IOTA, left-hand version, 3 A, 120 V, protective paint, Inter-Marshalling

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

VARIOFACE 16-channel module intended for use with Honeywell® Experion C300 24 V digital IOTA, left-hand version, 3 A, 120 V, conformal coating, inter-marshalling
Your advantages
UM-PRO housingDIN rail mounting, includes grounding footDesigned to be mounted in the left side of the cabinetPer channel pluggable 3 A fusingLED blown fuse indicationConformally-coated PCBPer channel configuration for NO or NC contactsPer-channel selectable inter-marshalling or external-powered (via toggle switch)Key Commercial Data
Orderkey 2906193
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4055626078038
Weight per Piece (excluding packing) 0.000 g
Custom tariff number 85369010
Country of origin US (United States)

Dimensions
Width 244 mm
Height 142.3 mm
Depth 66.8 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 70 °C
Ambient temperature (storage/transport) -40 °C ... 75 °C
Input data
Nominal input voltage UN 24 V DC
Input voltage range in reference to UN 0.8 ... 1.1
Typical input current at UN 7 mA
Typical response time 5 ms
Typical release time 15 ms
Type of protection Free-wheeling diode
Protective circuit/component Damping diode
Output data
Contact type 1 PDT
Contact material AgSnO
Maximum switching voltage 120 V AC/DC
Minimum switching voltage 12 V
Limiting continuous current 3 A (fuse limited)
Min. switching current 10 mA (at 12 V)
Interrupting rating (ohmic load) max. 72 W (24 V DC)
20 W (48 V DC)
18 W (60 V DC)
23 W (110 V DC)
360 VA (120 V AC)
Error detectio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-D37M/16RSC-24DC/DO/C3/L IMC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.