INDUSTRIAL COMPONENT DATA

UM-D37M/DS/FU/DI120V/C300/L IM 2905867 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-D37M/DS/FU/DI120V/C300/L IM



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-D37M/DS/FU/DI120V/C300/L IM
Catalog number	2905867
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-73B5068B1F
Generated	2026-11-19

Product Overview

Interface module
VARIOFACE module with 16 channels for use with Honeywell Experion C300 IOTA (high voltage, digital): CX-TDI110 and CX-TDI120. Execution on the left side.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2905867
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4055626081212
Weight per Piece (excluding packing) 0.000 g
Custom tariff number 85369010
Country of origin US (United States)
Dimensions
Width 120 mm
Height 142.3 mm
Depth 66.8 mm
Ambient conditions

Ambient temperature (operation) -40 °C ... 70 °C
Ambient temperature (storage/transport) -40 °C ... 75 °C
Connection data for connection 1
Connection name Field level
Connection method Screw connection with disconnect
Stripping length 8 mm
Screw thread M 3
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Connection data for connection 2
Connection name Controller level
Connection method D-SUB pin strip
Number of connections 1
Number of positions 37
Supported controller
Controller HONEYWELL Experion PKS C300/C-Series
- suitable I/O card TDI110 (non-redundant)
TDI120 (redundant)
Standards and Regulations
Standards/regulations DIN EN 50178
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss 5.127250313eCl@ss 7.027141152eCl@ss 8.027141152eCl@ss 9.027141152
ETIM 4.0EC002780ETIM 5.0EC002780ETIM 6.0EC002780
UNSPSC 13.239121432

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-D37M/DS/FU/DI120V/C300/L IM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.