INDUSTRIAL COMPONENT DATA

# UM-D37M/DS/FU/LED/AID4/C300/R 2905134 PHOENIX CONTACT Interface module

**Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-D37M/DS/FU/LED/AID4/C300/R**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | UM-D37M/DS/FU/LED/AID4/C300/R |
| Catalog number | 2905134 |
| Category | Interface module |
| Minimum order | 1 Pcs |
| Document ID | EO-045A5D47B2 |
| Generated | 2026-11-19 |

## Product Overview

Interface module
VARIOFACE module designed for the use of Honeywell Experion C300 16-channel analogue input cards. Channels 13.....16 have different inputs.
VARIOFACE module intended for use with Honeywell Experion C300 16-channel analog input cards. Channels 13.....16 feature differential inputs.

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > INTERFACE Components (IF) |

## Additional Product Information

Technical dataProduct propertiesProduct type Interface module
Product family VARIOFACE
Number of positions 37
No. of channels 16
Data management status
Article revision 00
Electrical propertiesNominal voltage UN 24 V DC
Max. current carrying capacity per branch 500 mA (fuse limited)
Supported controller HONEYWELL Experion PKS C300/C-Series
Suitable I/O card TAIX01 (non-redundant)
TAIX11 (redundant)

TAIX51 (non-redundant)
TAIX61 (redundant)
TAIN01 (non-redundant)
TAIN11 (redundant)
Supported controller HONEYWELL Experion LX Series 8
Suitable I/O card 8X-TAIXA1
8X-TAIXB1
Connection dataField level
Connection method Screw connection with disconnect knife
Stripping length 8 mm
Screw thread M 3
Conductor cross section rigid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Controller level
Connection method D-SUB pin strip
Number of connections 1
Number of positions 37
SignalingStatus display no
Status display present Yes, if the fuse fails
DimensionsItem dimensions
Width 124 mm
Height 142.3 mm
Depth 79 mm
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -40 °C ... 60 °C
Ambient temperature (storage/transport) -40 °C ... 75 °C
Standards and regulationsStandards/regulations DIN EN 50178
MountingMounting type DIN rail mounting
Assembly note in rows with zero spacing
Mounting position any
NotesGeneral Standard or halogen-free cables
Notes on operation For proper use, the specifications...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-D37M/DS/FU/LED/AID4/C300/R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.