INDUSTRIAL COMPONENT DATA

UM-D37M/DS/FU/LED/AO/C3/R C 2906187 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-D37M/DS/FU/LED/AO/C3/R C



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-D37M/DS/FU/LED/AO/C3/R C
Catalog number	2906187
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-9671141AE8
Generated	2026-11-19

Product Overview

Interface module
16-channel module for Honeywell C300 analog boards with separation, test points, 500 mA fuses, and fuse status indicator.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2906187
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4055626066844
Weight per Piece (excluding packing) 0.000 g
Custom tariff number 85369010
Country of origin US (United States)
Dimensions
Width 104 mm
Height 142.3 mm
Depth 79 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 60 °C

Ambient temperature (storage/transport) -40 °C ... 75 °C
General
Note Standard or halogen-free cables
Max. perm. operating voltage 24 V DC
Max. perm. current (per branch) 500 mA (fuse limited)
Max. permissible current (separate power supply) 4 A (via D-SUB)
Number of positions 37
Status display No
Connection data for connection 1
Connection name Field level
Connection method Screw connection with disconnect knife
Stripping length 8 mm
Screw thread M 3
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Connection data for connection 2
Connection name Controller level
Connection method D-SUB pin strip
Number of connections 1
Number of positions 37
Supported controller
Controller HONEYWELL Experion PKS C300/C-Series
- suitable I/O card TAOX01 (non-redundant)
TAOX11 (redundant)
TAOX51 (non-redundant)
TAOX61 (redundant)
TAON01 (non-redundant)
TAON11 (redundant)
Controller Honeywell Experion LX Series 8
- suitable I/O card 8X-TAOXA1
8X-TAOXB1
Standards and Regulations
Standards/regulations DIN EN 50178
Environmental Product Compliance
REACh SVHC Lead 7439-92-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-D37M/DS/FU/LED/AO/C3/R C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.