INDUSTRIAL COMPONENT DATA

UM-D37M/DS/FU/LED/DG/C3/R C 2906184 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-D37M/DS/FU/LED/DG/C3/R C



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-D37M/DS/FU/LED/DG/C3/R C
Catalog number	2906184
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-67CF8B2113
Generated	2026-11-18

Product Overview

Interface module
VARIOFACE module designed for the use of Honeywell Experion C300 16-channel digital cards:

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

VARIOFACE module intended for use with Honeywell Experion C300 16-channel digital cards:
Your advantages
These VARIOFACE modules are used in combination with the relevant front adaptersPer channel pluggable 1 A fusingUM-PRO housingDIN rail mountingLED blown fusing indicationConformal coating of PCBPer channel disconnects with test pointsKey Commercial Data
Orderkey 2906184
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4055626080666
Weight per Piece (excluding packing) 0.000 g
Custom tariff number 85369010
Country of origin US (United States)
Ambient conditions
Ambient temperature (operation) -40 °C ... 60 °C

Ambient temperature (storage/transport) -40 °C ... 75 °C
General
Max. perm. operating voltage 24 V DC
Max. perm. current (per branch) 1 A (fuse limited)
Number of positions 37
Status display No
Connection data for connection 1
Connection name Field level
Connection method Screw connection with disconnect knife
Stripping length 8 mm
Screw thread M 3
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Connection data for connection 2
Connection name Controller level
Connection method D-SUB pin strip
Number of connections 1
Number of positions 37
Supported controller
Controller HONEYWELL Experion PKS C300/C-Series
- suitable I/O card TDIL01 (non-redundant)
TDIL11 (redundant)
TDIL51 (non-redundant)
TDIL61 (redundant)
TDOB01 (non-redundant)
TDOB11 (redundant)
TDOB51 (non-redund...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-D37M/DS/FU/LED/DG/C3/R C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.