INDUSTRIAL COMPONENT DATA

UM-KS50/32-MR/21/ADV551/SO207 2311108 PHOENIX CONTACT Active module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-KS50/32-MR/21/ADV551/SO207



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-KS50/32-MR/21/ADV551/SO207
Catalog number	2311108
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-EF3811F5D5
Generated	2026-11-19

Product Overview

Active module
32-channel output relay module (1 normally open contact, optionally linked to potential) with spring connection, fuse (2 AT) and 50-pin system connector. Suitable for Yokogawa ADV 551 and ADV 561 cards.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2311108
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4046356145909
Weight per Piece (excluding packing) 871.000 g
Custom tariff number 85364190
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 267.5 mm
Height 127.5 mm

Depth 44 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Input data
Nominal input voltage UN 24 V DC
Input voltage range in reference to UN 0.9 ... 1.1
Typical input current at UN 7 mA (per channel)
Type of protection Damping diode, polarity protection
Protective circuit/component Damping diode, polarity protection diode
Operating voltage display Green LED
Status display/channel Yellow LED
Output data
Contact type 1 N/O contact
Contact material AgSnO
Maximum switching voltage 230 V AC
Limiting continuous current 2 A (Per channel, pluggable fuse (IEC 6012-3/IV, 2AT))
Maximum inrush current 8 A (Supply, (V1+, V2+), pluggable fuse (UL 248-14, 250 V, 8AT))
Min. switching current 100 mA
Interrupting rating (ohmic load) max. 48 W (at 24 V DC)
20 W (at 48 V DC)
18 W (at 60 V DC)
23 W (at 110 V DC)
40 W (at 220 V DC)
500 VA (for 250 V AC)
General
No. of channels 32
Degree of protection IP00
Mounting position any
Connection data for connection 1
Connection name Field level
Connection method Spring-cage connection
Conductor cross section solid 0.2 mm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-KS50/32-MR/21/ADV551/SO207 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.