INDUSTRIAL COMPONENT DATA

UM-PRO 108 L 7,40CM GY7035 BO 2203778 PHOENIX CONTACT Press-drawn section housings, Basic profile, profile w..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-PRO 108 L 7,40CM GY7035 BO



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-PRO 108 L 7,40CM GY7035 BO
Catalog number	2203778
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-5B586519E0
Generated	2026-11-18

Product Overview

Press-drawn section housings, Basic profile, profile width (internal): 108 mm, length: 74 mm, color: light gray (7035)
Extruded profile boxes, Locking with side elements, locking with floor element, Basic profile, colour: light grey (7035), profile width (inside): 108 mm, length: 74 mm, depth: 19.8 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2203778
Packing unit 1
GTIN 4055626431307
Custom tariff number 39169010
Product properties
Material specifications
PCB specifications
Environmental Product Compliance
Dimensions
Ambient conditions

Packaging specifications
Classifications
Product properties
Brief article description Profile
Type UM-PRO 108 L 7,40CM GY7035 BO
Order No. 2203778
Housing type Press-drawn section housings
Type Basic profile
Mounting type Latching with side elements, latching with foot element
Back to topDimensions
Length 74 mm
Profile PCB width (selectable): 108 mm [UM108]
Profile width (internal) 108 mm
Depth 19.8 mm
Back to topMaterial specifications
Housing material Polyamide
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 80 %
Back to topPCB specifications
PCB holders 3
PCB thickness 1.4 mm ... 1.8 mm
Mounting position parallel to the DIN rail
Type of PCB mount Insertion/securing with additional elements
Back to topPackaging specifications
Pieces per package 1
Denomination packing units Pcs.
Back to topEnvironmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Back to topClassifications
eCl@ss
eCl@ss 10....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-PRO 108 L 7,40CM GY7035 BO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.