INDUSTRIAL COMPONENT DATA

UM-S95U/S7/FLK50/PLC 2907030 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-S95U/S7/FLK50/PLC



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-S95U/S7/FLK50/PLC
Catalog number	2907030
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-0BD294EC77
Generated	2026-11-19

Product Overview

Passive module
VARIOFACE output module for Siemens SIMATIC® S5-95U, with a connector for 50-pin flat web cables in which an S7 control system can be attached, module width: 135 mm
VARIOFACE termination board for Siemens SIMATIC® S5-95U, with a 50-pos. flat-ribbon cable connector which can be connected to an S7 controller, module width: 135 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Technical dataProduct propertiesProduct type Interface module
Product family VARIOFACE
Data management status
Article revision 04
Insulation characteristics: Air clearances and creepage distances
Insulation Functional insulation
Overvoltage category II
Pollution degree 2
Electrical propertiesOperating voltage range 19.2 V DC ... 26.4 V DC
Current (per branch) <= 1 A
Current (Voltage supply per byte) <= 2 A

Air clearances and creepage distances
Rated insulation voltage 50 V
Rated surge voltage 0.5 kV (1.2/50 us)
Connection dataConnection 1 (control level)
Connection in acc. with standard IEC 60603-13
Connection method IDC/FLK pin strip
Number of connections 1
Number of positions 50
Insertion/withdrawal cycles > 50
Pitch 2.54 mm
Connection 2 (field level)
Connection method Spade connection
Number of positions 40
Note 2,8 x 0,8
Connection 3 (supply)
Connection method Screw connection
Stripping length 8 mm
Screw thread M3
Number of positions 3
Conductor cross section rigid 0.2 mm² ... 4 mm²
Conductor cross-section rigid (2 conductors with same cross section) 0.2 mm² ... 1.5 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
0.25 mm² ... 2.5 mm² (Ferrule without plastic sleeve)
0.25 mm² ... 2.5 mm² (Ferrule with plastic sleeve)
Conductor cross section flexible (2 conductors with same cross section) 0.2 mm² ... 1.5 mm²
0.25 mm² ... 0.75 mm² (Ferrule without plastic sleeve)
0.5 mm² ... 1.5 mm² (TWIN ferrule with plastic sleeve)
Conductor cross section AWG 24 ... 12
Tightening t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-S95U/S7/FLK50/PLC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.