INDUSTRIAL COMPONENT DATA

UM122-REL/MR-G220/B08/SO148 2306715 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM122-REL/MR-G220/B08/SO148

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	UM122-REL/MR-G220/B08/SO148
Catalog number	2306715
Category	Switching relay
Minimum order	5 Pcs
Document ID	EO-028A6A370F
Generated	2026-11-19

Product Overview

Relay Module
VARIOFACE module, customer-specified connection, mini-switching relay for 110 V DC with light indication

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2306715
Packing unit 1 pc
Minimum order quantity 5 pc
Note Made to Order (non-returnable)
GTIN 4046356039659
Weight per Piece (excluding packing) 590.900 g
Custom tariff number 85364900
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 141 mm
Height 128 mm

Depth 51 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C
General
Mechanical service life approx. 3x 107cycles
Mounting position any
Connection data for connection 1
Connection name Input
Connection method Screw connection
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Connection data for connection 2
Connection name Output
Connection method Screw connection
Conductor cross section solid 0.2 mm² ... 2.4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Standards and Regulations
Designation Air clearances and creepage distances, input/output
Standards/regulations DIN EN 50178: 1998-04
Rated insulation voltage 230 V
Rated surge voltage 4 kV (1.2/50 us)
Insulation Basic insulation
Degree of pollution 2
Overvoltage category III
Designation Air and creepage distances, output/output
Standards/regulations DIN EN 50178: 1998-04
Rated insulation voltage 260 V
Rated surge voltage 2.3 kV (1.2/50 us)
Insulation Functional insulation
Degree of pollutio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM122-REL/MR-G220/B08/SO148 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.